

## ФИЛТРИ Y-STRAINERS



**Филтър на фланци - PN16**  
Y-Strainer - Flanged - PN16

Тип - Type : Fig. 821A		Материал Material EN-GJL-250 Tmax=300°C		Материал : GG25, Епоксидно боядисан Material : GG25, Epoxy painted	
DN	Дълж. Leng	Отвор Screen	Код Code	Код Code	Код Code
15	130	1 mm	260504	260604	260604
20	150	1 mm	260505	260605	260605
25	160	1 mm	260506	260606	260606
32	180	1 mm	260507	260607	260607
40	200	1 mm	260508	260608	260608
50	230	1 mm	260509	260609	260609
65	290	1.25 mm	260510	260610	260610
80	310	1.25 mm	260511	260611	260611
100	350	1.6 mm	260512	260612	260612
125	400	1.6 mm	260513	260613	260613
150	480	1.6 mm	260514	260614	260614
200	600	1.6 mm	260515	260615	260615
250	730	1.6 mm	260516	260616	260616
300	850	1.6 mm	260517	260617	260617



**Филтър на фланци : PN40**  
Y-Strainer; Flanged : PN40

**Филтър с резба : PN16**  
Y-Strainer; Threaded : PN16

Тип - Type : Fig. 821F				Тип - Type : Fig. 823A		
Материал - Material : GP240GH Tmax=400°C				Материал - Material : EN-GJL-250 Tmax=200°C		
DN	KVs m3/h	Отвор Screen	Код Code	KVs m3/h	Дълж. Leng	Код Code
15	5.7	1 mm	220704	3.6	85	260404
20	10.4	1 mm	220705	11	100	260405
25	16.4	1 mm	220706	15.5	120	260406
32	27.03	1 mm	220707	26	140	260407
40	42	1 mm	220708	41	160	260408
50	64.7	1 mm	220709	68	205	260409
65	96	1.25 mm	220710			
80	149	1.25 mm	220711			
100	223	1.25 mm	220712			
125	347	1.25 mm	220713			
150	480	1.25 mm	220714			
200	853	1.6 mm	220715			