

UNIGAS

Stainless steel flexible extensible joints.

The external polyolefin heat-shrinking is flame-proof and non-toxic, used for the gas/water system connections from boilers, water heaters, etc etc...



CHRYSsafidis

TYPE	CODE	THREAD	DN	LENGHT min/max	Pieces for box
M.F. - F.G.	70120	1/2"	15	75/130	18
M.F. - F.G.	70121	1/2"	15	100/200	18
M.F. - F.G.	70122	1/2"	15	200/400	18
M.F. - F.G.	70123	1/2"	15	260/480	18
TYPE	CODE	THREAD	DN	LENGHT min/max	Pieces for box
M.F. - F.G.	70200	3/4"	20	75/130	18
M.F. - F.G.	70201	3/4"	20	100/200	18
M.F. - F.G.	70202	3/4"	20	200/400	18
M.F. - F.G.	70203	3/4"	20	260/520	18
TYPE	CODE	THREAD	DN	LENGHT min/max	Pieces for box
M.F. - F.G.	70204	1/2" 3/4"	15	75/130	18
M.F. - F.G.	70205	1/2" 3/4"	15	100/200	18
M.F. - F.G.	70206	1/2" 3/4"	15	200/400	18
M.F. - F.G.	70207	1/2" 3/4"	15	260/520	18
TYPE	CODE	THREAD	DN	LENGHT min/max	Pieces for box
M.F. - F.G.	70250	1"	25	75/130	18
M.F. - F.G.	70251	1"	25	100/200	18
M.F. - F.G.	70252	1"	25	200/400	18
M.F. - F.G.	70253	1"	25	260/520	18

## TECHNICAL CARD

TUBE	STAINLESS STEEL AISI 316 TO PARALLEL WAVES	PROTECTION SHEAT	PLASTIC MATERIAL FLAME-PROOF, NON TOXIC YELLOW COLOUR
THICKNESS	0,21 mm.	GASKETS	RUBBER NORMATIVE EN 549
MALE	HI SPEED STAINLESS STEEL AISI 303	TERMIC TREATMENT	SOLUBILIZED TUBE
THREAD MALE	NORMATIVE EN 10226-2	WELDING	TIG WELDING WITHOUT ANY CONTRIBUTION OF MATERIAL CHECKED AT MOSPHERE ACCORDING TO THE NORMATIVE EN 1418
ENDFITTING NUT CARRIER	HI SPEED STAINLESS STEEL AISI 303	EXERCISE TEMPERATURE	-10° / +90°
NUT	BRASS NORMATIVE EN 12164/12165	APPLICATION	STATIC
NUT THREAD	NORMATIVE EN ISO 228-1		

## MAXIMUM EXERCISE PRESSURE TABLE

DIAMETER	DN 15	DN 20	DN 25	DN 32	DN 40	DN 50
GAS USE	0,5 BAR	0,5 BAR	0,5 BAR	0,5 BAR	0,5 BAR	0,5 BAR
WATER USE	8 BAR	8 BAR	8 BAR	8 BAR	8 BAR	8 BAR

## CURVATURE MINIMUM RANGE TABLE

DIAMETER	DN 15	DN 20	DN 25	DN 32	DN 40	DN 50
MINIMUM RANGE IN MM.	30	40	45	50	55	60